AMENDMENTS TO THE CLAIMS

Docket No.: 14113-00010-US

- 1. (Original) Organic electroluminescent device comprising an anode, a cathode and at least one emission layer comprising at least one matrix material which is doped with at least one phosphorescent emitter, characterised in that the emission layer on the anode side is directly adjacent to an electrically conductive layer.
- 2. (Original) Organic electroluminescent device according to Claim 1, characterised in that either the matrix material or the phosphorescent emitter is a low-molecular-weight defined compound having a molecular weight of less than 10,000 g/mol.
- 3. (Original) Organic electroluminescent device according to Claim 2, characterised in that both the matrix material and the phosphorescent emitter are low-molecular-weight defined compounds having a molecular weight of less than 10,000 g/mol.
- 4. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 3 claim 1, characterised in that the electrically conductive layer to which the emission layer on the anode side is adjacent is an organic or organometallic hole-injection layer.
- 5. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 3 claim 1, characterised in that the electrically conductive layer to which the emission layer on the anode side is adjacent is the anode.
- 6. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 5 claim 1, characterised in that it comprises further layers.
- 7. (Original) Organic electroluminescent device according to Claim 6, characterised in that the further layers are one or more hole-blocking layers and/or electron-transport layers and/or electron-injection layers.
- 8. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 7 claim 1, characterised in that the emission layer is directly adjacent to the electron-transport layer without the use of a hole-blocking layer.

9. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 7 claim 1, characterised in that the emission layer is directly adjacent to the cathode or the electron-injection layer without the use of a hole-blocking layer and without the use of an electron-transport layer.

Docket No.: 14113-00010-US

- 10. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 9 claim 1, characterised in that more than one emission layer is present.
- 11. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 10 claim 1, characterised in that the emission layer has a layer thickness of 1 to 300 nm.
- 12. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 10 claim 1, characterised in that the phosphorescent emitter present is a compound which contains at least one atom having an atomic number of greater than 36 and less than 84.
- 13. (Original) Organic electroluminescent device according to Claim 12, characterised in that the phosphorescent emitter comprises at least one element selected from molybdenum, tungsten, rhenium, ruthenium, osmium, rhodium, iridium, palladium, platinum, silver, gold or europium.
- 14. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 13 claim 1, characterised in that the degree of doping of the phosphorescent emitter in the matrix is 0.5 to 50%.
- 15. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 14claim 1, characterised in that the glass transition temperature T_g of the matrix material is greater than 100°C.
- 16. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 15 claim 1, characterised in that the matrix material has an absorbance of less than 0.2 in the visible spectral region between 380 nm and 750 nm at a film thickness of 30 nm.

17. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 16_claim 1, characterised in that the lowest triplet energy of the matrix material is between 2 and 4 eV.

Docket No.: 14113-00010-US

- 18. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 17claim 1, characterised in that the matrix material is an electron-conducting compound.
- 19. (Original) Organic electroluminescent device according to Claim 18, characterised in that the matrix material exhibits predominantly reversible reduction or forms predominantly stable free-radical anions.
- 20. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 19 claim 1, characterised in that the electron mobility of the matrix material is between 10⁻¹⁰ and 1 cm²/V·s.
- 21. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 20 claim 1, characterised in that the matrix material is selected from the classes of ketones, imines, phosphine oxides, phosphine sulfides, phosphine selenides, phosphine selenides, sulfones and sulfoxides ketone, imine, phosphine oxide, phosphine sulfide, phosphine selenide, phosphazene, sulfone or sulfoxide, preferably with aromatic substituents.
- 22. (Currently amended) Organic electroluminescent device according to Claim 21, characterised in that the matrix materials is ketone, phosphine oxide or sulfoxide are selected from the classes of ketones, phosphine oxides and sulfoxides.
- 23. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 22 claim 1, characterised in that one or more layers are coated by a sublimation process.
- 24. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 22claim 1, characterised in that one or more layers are coated by the organic vapour phase deposition (OVPD) process or with the aid of carrier-gas sublimation.

25. (Currently amended) Organic electroluminescent device according to one or more of Claims 1 to 22 claim 1, characterised in that one or more layers are coated by the LITI (light induced thermal imaging) process.

Docket No.: 14113-00010-US

- 26. (Currently amended) Organic solar <u>cell which comprises the organic electroluminescent</u> device as claimed in claim 1 cell, characterised in that the structure corresponds to one or more of Claims 1 to 25.
- 27. (Currently amended) Organic laser <u>diode which comprises the organic</u> <u>electroluminescent device as claimed in claim 1 diode, characterised in that the structure corresponds to one or more of Claims 1 to 25.</u>